



QG 36W Universal IEC62368-1 AC/DC Adapter 36W



Product Highlights:

- Low cost ;
- Ultra Small Size ;
- Energy Efficiency;
- Suit LED Lighting, Display or Photo Frame, Network and USB Devices

Protection :

- Short Circuit Protection ;
- Over Voltage Protection ;
- Over Current Protection ;

Safety Standard :

- 60950-1 ;
- 62368-1 ;
- PSE 别表第八

Efficiency :

- Energy Efficiency Level VI(ErP/DoE)
- Meet COMMISSION REGULATION(EU) 2019/1782
- Meet DOE10 CFR Part 429 and 430

Emissions:


- FCC Part 15 class B
- VCCI Class B
- CE CISPR 32 EN55032
- BS EN 55032

Immunity:

- EN 55035
- BS EN 55035

Electrical Spec:

External dimensions:



Input					
Description	Min	Typ.	Max.	Units	Comment
Voltage	90	100~240	264	Vac	
Frequency	47	50/60	63	Hz	

Description	Min	Typ.	Max.	Units	Comment
Operating Temperature	0	-	40	°C	
Storage Temperture	-20	-	65	°C	
Operating Humidity	5	-	95	%RH	
Storage Humidity	5	-	95	%RH	

Typical model list:

output voltage	output current	precision	Ripple	Noise	Efficiency	No-Load
5.0V	4.0A	±5%	240mV	240mV	83.08%	0.1W
12.0V	2.5A	±5%	240mV	240mV	86.95%	0.1W
12.0V	3.0A	±5%	240mV	240mV	87.40%	0.1W
15.0V	2.4A	±5%	240mV	300mV	87.40%	0.1W
16.0V	2.2A	±5%	240mV	240mV	87.36%	0.1W
18.0V	2.0A	±5%	240mV	240mV	87.40%	0.1W
24.0V	1.5A	±5%	240mV	240mV	87.40%	0.1W
36.0V	1.0A	±5%	240mV	240mV	87.40%	0.1W

■ Measurement Condition

1.Measurements shall be made with an oscilloscope with 20MHz bandwidth.

2.Outputs shall be bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system load

工厂地址: 东莞市石排镇水吉吉安路8号良益工业大厦B座5-6楼

公司电话: 0769-81818091

销售电话: 180-2897-1545

公司网站: www.nexgen-power.com

业务邮箱: alex@nexgen-power.com